


PRIME


Complete Family of Architectural Point Source Solutions

The Prime Series is engineered for precise light control with hot aiming, supported by a wide range of optics, filters, and wattage options. Available in 2", 3", 4", and 6" apertures for seamless integration across a variety of ceiling types.

Non-IC - New Construction



IC Air-Tight - New Construction



Prime Remodel



Fixed



DOWNLIGHT

Fixed



WALL WASH

0°-40°
Hot Aiming



ADJUSTABLE

LUMENS

2" 599-2070 lm

2700K, 3000K, 3500K, 4000K, Warm Dim, Amber

12° 30° 35° 40° 50°

3" 586-2785 lm

2700K, 3000K, 3500K, 4000K, Warm Dim, Amber

12° 25° 30° 40° 50° 70°

4" 650-5310 lm

2700K, 3000K, 3500K, 4000K, Warm Dim, Amber

15° 24° 30° 35° 40° 50° 70°

6"* 730-6427 lm

2700K, 3000K, 3500K, 4000K, Warm Dim, Amber

15° 24° 30° 35° 40° 50° 75°

* Prime Remodel is not available in 6"

BINNING

2-Step Binning

CRI

90+

FILTERS

Frosted, Solite, Honeycomb, Linear

HOUSING TYPE

Non IC, IC Air-Tight, Remodel, Super Shallow, Specialty Ceiling, Chicago Plenum

DRIVER SELECTION

Standard All-Inclusive TRIAC (120V), ELV (120V), 0-10V (120-277V); eldoLED, Lutron; DALI

RATING

CSA Listed, Wet Location, IC Air-Tight, Chicago Plenum, Title24, JA8

FLANGELESS PLASTER

Utilization of a mud-in plaster ring for a flush, trimless appearance. Hardware is plastered directly into drywall.

FLANGELESS MILLWORK

Millwork Adapter: Connects flangeless trims to collar

Dedicated Collar: Dedicated collar for direct trim installation

ROUND



Flange Downlight



Flange Accent



Flange Pinhole



Flangeless Downlight



Flangeless Accent



Flangeless Pinhole

SQUARE



Flange Downlight



Flange Accent



Flange Pinhole



Flangeless Downlight



Flangeless Accent



Flangeless Pinhole



White



Black



Haze



Bronze



Clear



Wheat

*Consult Factory for Made to Order Finishes

LED TECHNOLOGY


High-precision 90+ CRI LEDs with 2-step MacAdam binning. Available in Static White, Warm Dim, and Amber



PRECISE OPTICS

Intersect Optics provides advanced beam control and delivers distribution from 12° to 75°

12° — 75°



OPTICAL FILTERS

Available in Frosted, Honeycomb, Solite, and Linear options.

FIELD REMOVABLE LENS



Standard



- Not suitable for wet location
- Increase in lumens by \approx 7%

SUPER SHALLOW

Designed for new construction applications, this IC-Rated housing features a 2.5" profile, making it ideal for limited plenum space.



UNIVERSAL BAR HANGER

- Length adjustable up to 27"
- Compatible with Wood mount, T-Bar, C-Channel



WIRELESS CONTROLS

An agnostic platform compatible with leading wireless ecosystems, including Lutron Athena and other networked controls.

EMERGENCY OPTIONS

Available with **4W**, **8W**, or **15W** emergency battery solutions delivering up to 1,500 lumens for a minimum of 90 minutes. Select configurations are accessible from below the ceiling for easy maintenance.

PRIME

PRIME functions as an integrated lighting system, providing dedicated solutions across a wide range of ceiling types and architectural conditions while maintaining consistent light output, visual continuity, and performance throughout a space.

