



PRODIGY

Architectural Fire-Rated Led Downlight

Prodigy embodies an architectural essence in a compact all-in-one form factor. Available in fixed, wall wash, or adjustable configurations, this value-driven solution balances high-performance features with a competitive price point.

ADJUSTABLE BAR HANGER

Wood mount, T-Bar, and C-Channel

ADJUSTABLE HEIGHT

Easy height adjustment

DIMENSIONS

6" (L) x 7 1/4" (W) x 4 1/8" (H)

OPTIONAL INTEGRAL EMERGENCY BATTERY

Removable from below the ceiling

DOWNLIGHT

WALL WASH

ADJUSTABLE

LUMENS

738 Lm–1713 Lm

COLOR TEMPERATURE

2700K, 3000K, 3500K, 4000K, Warm Dim

CRI

90+

BINNING

2-Step Binning

OPTICAL DISTRIBUTION

18°, 25°, 30°, 40°, 50°, 80°

FILTERS

Frosted, Solite, Honeycomb

HOUSING TYPE

IC Air-Tight New Construction, Chicago Plenum, and Fire-Rated

DRIVER SELECTION

Standard All-Inclusive TRIAC (120V), ELV (120V), 0–10V (120–277V); eldoLED; DALI

RATING

Fire Rated, Wet Location, IC air-tight, Chicago Plenum, Title24, JA8

ROUND



Flange Downlight



Flange Wall Wash



Flange Pinhole



Flange Parabolic



Flangeless Downlight



Flangeless Wall Wash



Flangeless Pinhole



Flangeless Parabolic

SQUARE



Flange Downlight



Flange Wall Wash



Flange Pinhole



Flangeless Downlight



Flangeless Wall Wash



Flangeless Pinhole



IC

Air-tight

CHICAGO

PLENUM



2 HOUR

FIRE RATED



TITLE24

Compliant



JAB

Compliant

PATENT PENDING

integer
Lights

For more information, visit www.integerlights.com.