

2" LED ARCHITECTURAL ROUND FLANGELESS ADJUSTABLE

NEW CONSTRUCTION: IC & NON IC



GENERAL INFORMATION

USE OF PRODUCT

The 2" Prime Adjustable is a small aperture fixture with shallow height that may be used in residential and commercial applications. Die cast trims, with an assortment of color temperatures, optics and dimmable drivers available.

LED ENGINE

LED engine available with CREE LEDs in 2700K, 3000K, 3500K, or 4000K in standard 93+ CRI. 2 Step MacAdam ellipse allows for color consistency between fixtures. LED mounted to aluminum heat sink for maximum life output and thermal management. LED engine is accessible from below ceiling.

OPTICAL LENS

Field replaceable optical lenses are available in 17°, 35°, 40°, 50°, and 55°. Easily achieve narrow spot to wide flood beam pattern.

THERMAL MANAGEMENT

Ambient temperatures at fixture location should not exceed -20° to 40°C.

GENERAL PERFORMANCE CHART

*Detailed performance chart may be found on page 2


	6W	9W	12W	15W	20W
Initial Lumens	657/955	890/1296	1122/1618	1267/2015	1485/2422
Delivered Lumens	537-678	729-926	920-1171	1020-1452	1199-1756

* Values are listed at 3000K, 90+ CRI with a white bevel & trim.

Delivered lumens range based on beam spread.

Performance may vary +/- 5%

BEAM SPREAD



- Field replaceable TIR optics
- Easily achieve narrow spot to wide flood beam pattern
- Optional filters available upon request

PRIME FAMILY OF PRODUCTS




Downlight




TechZone®



WoodWorks®



Multiple Dedicated Bevel



Multiple Open Bevel



Cylinder



Square Luminaire

2" LED ARCHITECTURAL ROUND FLANGELESS ADJUSTABLE

NEW CONSTRUCTION: IC & NON IC

ORDERING INFORMATION

Series	Wattage	Dimming	Color Temperature	Optical Lens	Filter	Housing Type
RPA2	6W - 6 Watt	ID ¹ - Standard All-Inclusive ELV(120V), Triac(120V), and 0-10V(120-277V)	27K - 2700K	17 ⁴ - 17°	Blank - None	IC - IC Air-Tight New Construction
	9W - 9 Watt		30K - 3000K	35 - 35°	F - Frosted Filter	NC - Non-IC New Construction
	12W - 12 Watt	Dimming Driver (Intelligent Drive)	35K - 3500K	40 - 40°	H - Honey Comb	
	15W - 15 Watt	EEIS ² - eldoLED 1% Dim 0-10V (120-127V), Triac (120V)	40K - 4000K	50 - 50°	S - Solite Filter	
	20W - 20 Watt	EDIO ³ - eldoLED 0.1% Dim (0-10V) EDID ⁴ - eldoLED 0.1% Dim (DALI) EDD ⁵ - eldoLED 1% Dim (DALI2) PEQQ - Lutron Hi-Lume Premier Ecosystem 0.1% with Soft-on, Fade-to-Black Dimming		55 - 55°	L - Linear Filter	

Collar	Module Type	Trim Style	Frame Accessories	Options
CR10 - 1.0" Depth	AMH - Adjustable	LPR - Flangeless Plaster	UH - Universal Bar Hanger	ER4W ⁵ - Emergency Battery with Remote test switch (400 lm)
CR15 - 1.5" Depth		LAMR - Flangeless Millwork with Adapter	C - C-Channel Bar Hanger	ER8W ⁶ - Emergency Battery with Remote test switch (800 lm)
MTO - Made To Order		LDMR - Flangeless Millwork with Dedicated Collar		ER15W ⁶ - Emergency Battery with Remote test switch (1,500 lm)
				347V - 347V Step down transformer
				CP ⁷ - Chicago Plenum

TRIM ORDERING INFORMATION

DIE-CAST

Bevel Finish	Bevel	Finish	Notes
2" Round Flangeless Open	2RLO-CL 2RLO-CL 2RLO-CL 2RLO-CL 2RLO-CL 2RLO-CL	W - White B - Black H - Haze BZ - Bronze MTO - Made To Order	<ol style="list-style-type: none"> 1. Intelligent Drive is the standard driver. 2. Programmable only in linear mode. 3. Must specify logarithmic or linear eldoLED diver. 4. 17° spread without lens on trim. 5. Available in IC housing only. 6. Ceiling access is required for IC housing to replace the EM unit. 7. Requires IC housing.
2" Round Flangeless Accent	2RLA-CL 2RLA-CL 2RLA-CL 2RLA-CL 2RLA-CL 2RLA-CL	W - White B - Black H - Haze BZ - Bronze MTO - Made To Order	

2" LED ARCHITECTURAL ROUND FLANGELESS ADJUSTABLE

NEW CONSTRUCTION: IC & NON IC


PERFORMANCE CHART

Optics	¹ 17°	35°	40°	50°	55°
6W	Initial Lumens	657	955	955	955
	Delivered Lumens	537	645	675	672
	UGR		16.8	17	20
9W	Initial Lumens	890	1296	1296	1296
	Delivered Lumens	729	885	925	926
	UGR		18.2	18.3	21.2
12W	Initial Lumens	1122	1618	1618	1618
	Delivered Lumens	920	1123	1171	1170
	UGR		18.7	18.8	22.2
15W	Initial Lumens	1267	2015	2015	2015
	Delivered Lumens	1020	1371	1410	1452
	UGR		19.5	19.6	21.1
20W	Initial Lumens	1485	2422	2422	2422
	Delivered Lumens	1199	1662	1706	1756
	UGR		20.2	20.3	21.7

* Values are listed at 3000K, 90+ CRI with a white bevel & trim.

Notes

1. 17° spread without lens or trim

COLOR TEMPERATURE MULTIPLIER FOR DELIVERED LUMENS**DIFFUSED LENS**

- Listed IES files are with diffused lens




OPTIONAL FIELD REMOVABLE LENS

- Not suitable for wet locations
- Increase in lumens by approximately 7%

2" LED ARCHITECTURAL ROUND FLANGELESS ADJUSTABLE




NEW CONSTRUCTION: IC & NON IC

NON-IC HOUSING DIMENSIONS



1. Must remove spacer to achieve 1 1/2" collar height
2. Consult factory for Made to Order collar height
3. Allow 1/8" tolerance

IC HOUSING DIMENSIONS




1. Must remove spacer to achieve 1 1/2" collar height
2. Consult factory for Made to Order collar height
3. Allow 1/8" tolerance

FRAME ACCESSORIES


UNIVERSAL BAR HANGER

COMPATIBLE CEILING

- Hat Channel
- T-Bar
- C-Channel
- Laminated Wood
- Quick-Span
- I-Beam
- Standard Joist




C-CHANNEL BAR HANGER



2" LED ARCHITECTURAL ROUND FLANGELESS ADJUSTABLE

NEW CONSTRUCTION: IC & NON IC

MODULE DIMENSIONS




FILTERS



Frosted Filter



Honey Comb






Solite Filter



Linear Filter







2" LED ARCHITECTURAL ROUND FLANGELESS ADJUSTABLE

NEW CONSTRUCTION: IC & NON IC

FLANGELESS PLASTER (LPR)**FLANGELESS MILLWORK WITH ADAPTER (LAMR)****FLANGELESS MILLWORK WITH DEDICATED COLLAR (LDMR)**

2" LED ARCHITECTURAL ROUND FLANGELESS ADJUSTABLE

NEW CONSTRUCTION: IC & NON IC

TRIM DIMENSIONS**TRIM FINISH**

White



Black



Haze




Bronze

*Consult Factory for Made to Order Finishes


2" LED ARCHITECTURAL ROUND FLANGELESS ADJUSTABLE

NEW CONSTRUCTION: IC & NON IC

REMOTE EMERGENCY BATTERY: NON-IC NEW CONSTRUCTION HOUSING**NC** - Non-IC New Construction


ER8W and **ER15W** is an 8W and 15W Emergency Battery that is remote to the fixture with a remote test switch. The EM unit is accessible from below the ceiling for replacement purposes.

1. Remote Emergency Battery
2. Remote Test Switch

REMOTE EMERGENCY BATTERY: IC NEW CONSTRUCTION HOUSING**IC** - IC Air-Tight New Construction

ER8W and **ER15W** is an 8W and 15W Emergency Battery that is remote to the fixture with a remote test switch. Ceiling access is required for replacement purposes

1. Remote Emergency Battery
2. Remote Test Switch

INTEGRAL EMERGENCY BATTERY: IC NEW CONSTRUCTION HOUSING**IC** - IC Air-Tight New Construction

ER4W is an 4W Emergency Battery that is integral to the fixture with a remote test switch. The EM unit is accessible from below the ceiling for replacement purposes.

*Available in IC housing only

1. Integral Emergency Battery
2. Remote Test Switch