**USE OF PRODUCT**

The 3" Prime architectural recessed multiple series offers a variety of lumens, color temperatures, beam angles, and filter options that may be modified in the field. Modules are available in bevel, regress, or snoot appearance.

**LED ENGINE**

LED engine available with CREE LEDs in 2700K, 3000K, 3500K, or 4000K in standard 90+ CRI. 2-step MacAdam ellipse allows for color consistency between fixtures. The LED is mounted to an aluminum heat sink for maximum life output and thermal management. LED engine is accessible from below the ceiling.

**FRAME CONSTRUCTION**

Housing is constructed from a 20-gauge powder-coated cold-rolled steel frame. Butterfly brackets available to accommodate adjustable, c-channel, and flat bar hanger (order separately).

**ADJUSTMENT**

0-40° Hot aiming.

**OPTICAL LENS**

Field replaceable total internal reflection (TIR) available in 18°, 30°, 50°, and 80°. Easily achieve narrow spot to wide flood beam pattern. Available filters include frosted, honeycomb, or solite.

**DIMMING**

Available in six driver selections. (ID) Standard all-inclusive ELV (120V), Triac (120V), and 0-10V (120-277V) dimming driver called Intelligent Drive, 120-277V. (LDE1) Lutron Hi-Lume 1% Ecosystem with soft-on, fade-to-black dimming, 120-277V. (L3DA) Hi-lume 1% EcoSystem/3-Wire L3D Driver (EEI) eldoLED Eco 1% Dim (0-10V), 120-277V. (EDIO) eldoLED Solo 0.1% Dim (DALI), 120-277V. Driver accessible from below ceiling.

**THERMAL MANAGEMENT**

Fixture location ambient temperature should not exceed -20° to 40°C.

**EMERGENCY BATTERY**

Optional emergency battery available for a minimum of 90 minutes with remote test switch in 800 delivered lumens.

**LABELS/COMPLIANCE/WARRANTY**

- CSA listed for US and Canada.
- Energy Star certified product.
- Dry/Damp/Wet location rated.
- State of California Title 24 and JA8 compliant.
- 5-year limited warranty.

**ORDERING INFORMATION**

Series	Aperture Size	Aperture Type	Module Configuration	Lumens Per Module	Color Temp.	Voltage	Dimming
RPA - Prime Series	3 - 3"	DB - Dedicated Bevel	1 - One Module	8L - 800 lm	27 - 2700K	UNV - 120-277	ID <sup>1</sup> - Standard All-Inclusive ELV, Triac, and 0-10V Dimming Driver (Intelligent Drive)
			2 - Two Module	11L - 1175 lm	30 - 3000K	120 - 120V	LDE1 <sup>2</sup> - Lutron Hi-Lume 1% Ecosystem with Soft-on, Fade-to-Black Dimming
			3 - Three Module	16L - 1650 lm	35 - 3500K		L3DA - Hi-lume 1% EcoSystem/3-Wire L3D Driver
			MTO - Made To Order		40 - 4000K		EEI <sup>2</sup> - eldoLED Eco 1% Dim (0-10V)
							EDIO <sup>2,3</sup> - eldoLED Solo 0.1% Dim (0-10V)
							EDID <sup>2,3</sup> - eldoLED Solo 0.1% Dim (DALI)


Optical Lens	Filter	Housing Type	Aperture	Frame Accessories	Options
18 - 18°	None - Included	IC - IC Air-Tight New Construction	SLAP - Square Flangeless	UH - Universal Bar Hanger	ER8 <sup>2</sup> - Emergency Battery with
30 - 30°	F - Frosted Filter	NC - Non-IC New Construction	Adjustable Plaster	C - C-Channel Bar Hanger	Remote Switch (800 lm)
50 - 50°	H - Honey Comb	ICP - IC New Construction	SLAM - Square Flangeless		
80 - 80°	S - Solite Filter	Chicago Plenum	Adjustable Millwork		

**TRIM ORDERING INFORMATION**







Aperture Size / Shape / Trim Type / Style	Bevel Opening	Bevel
3SLO - 3" Square Flangeless Open	Die-cast	CL - Die-cast Large Opening

**Notes**

1. Intelligent Drive is the standard driver.
2. Ceiling access required.
3. Must specify logarithmic or linear eldoLED driver.

**TRIM DIMENSIONS**

Large Opening

**HOUSING DIMENSIONS****ADJUSTMENT****FRAME ACCESSORIES****UNIVERSAL BAR HANGER****C-CHANNEL BAR HANGER**