

3" LED ARCHITECTURAL ROUND FLANGE WALL WASH

NEW CONSTRUCTION: IC & NON IC



GENERAL INFORMATION

USE OF PRODUCT

The 3" Prime Wall Wash is a small aperture fixture with a shallow housing height of 4 3/4", which is ideal for residential and commercial applications. Available options include die-cast or spun aluminum trims, various color temperatures, optics, filters, and dimmable drivers.

LED ENGINE

LED engine available in 2700K, 3000K, 3500K, or 4000K in standard 90+ CRI. 2-step MacAdam ellipse allows for color consistency between fixtures. The LED is mounted to an aluminum heat sink for maximum life output and thermal management. LED engine is accessible from below the ceiling.

OPTICAL LENS

Field replaceable optical lenses are available in 15°, 24°, 36°, 50°, and 80°. Easily achieve narrow spot to wide flood beam pattern.

FRAME CONSTRUCTION

IC and Non-IC rated housing are constructed from a 16-gauge heavy-duty, powder-coated cold-rolled steel frame and includes a junction box with 1/2" knockouts. Butterfly brackets (included) accommodate universal or C-channel hangers (order separately).

ADJUSTMENT

- Light engine locked at 20° tilt, consult factory for other tilt settings.
- Housing supports 359° locking rotation.
- Aperture collar compatible up to 1 1/2" ceiling thickness. Consult factory for made-to-order aperture collars exceeding 1 1/2".

DIMMING

Available in nine driver selections. (ID) Standard all-inclusive ELV (120V), Triac (120V), and 0-10V (120-277V) dimming driver called Intelligent Drive, (EEI) eldoLED 1% Dim 0-10V, (EEIS) eldoLED 1% Dim 0-10V (120-277V) and Triac (120V), Max 20W, (EDIO) eldoLED 0.1 Dim 0-10V, (EDID) eldoLED 0.1% Dim DALI, (EDD) eldoLED 1% Dim DALI2, (LDE1) Lutron Hi-Lume 1% Ecosystem with Soft-on, Fade-to-Black Dimming, (L3DA) Hi-Lume 1% Ecosystem/3-Wire L3D Driver, (PEQ0) Lutron Hi-Lume Premier Ecosystem 0.1% with Soft-on, Fade-to-Black Dimming.

GENERAL PERFORMANCE CHART

*Detailed performance chart may be found on page 3


	6W	9W	12W	15W	20W	24W	28W	32W
Initial Lumens	955	1296	1618	2015	2422	2799	3128	3405
Delivered Lumens	417-659	815-899	709-1134	865-1365	1024-1660	1221-1948	1372-2249	1549-2582

* Values are listed at 3000K, 90+ CRI with a white bevel & trim.

Delivered lumens range based on beam spread.

Performance may vary +/- 5%

BEAM SPREAD



Field replaceable TIR optics

PRIME FAMILY OF PRODUCTS




Downlight



TechZone®



WoodWorks®



Multiple Dedicated Bevel



Multiple Open Bevel



Cylinder



Square Luminaire

3" LED ARCHITECTURAL ROUND FLANGE WALL WASH

NEW CONSTRUCTION: IC & NON IC

ORDERING INFORMATION

Series	Wattage	Dimming	Color Temperature	Optical Lens	Housing Type
RPA3	6W - 6 Watt	ID ² - Standard All-Inclusive ELV, Triac, and 0-10V Dimming Driver (Intelligent Drive)	27K - 2700K	15 - 15°	IC ⁶ - IC Air-Tight New Construction
	9W - 9 Watt		30K - 3000K	24 - 24°	NC - Non-IC New Construction
	12W - 12 Watt	EEI ³ - eldoLED 1% Dim (0-10V)	35K - 3500K	36 - 36°	
	15W - 15 Watt	EEIS ⁴ - eldoLED 1% Dim 0-10V (120-277V), Triac (120V), Max 20W	40K - 4000K	50 - 50°	
	20W - 20 Watt			80 - 80°	
	24W - 24 Watt	EDIO ³ - eldoLED 0.1% Dim (0-10V)			
	28W ¹ - 28 Watt	EDID ³ - eldoLED 0.1% Dim (DALI)			
	32W ¹ - 32 Watt	EDD ³ - eldoLED 1% Dim (DALI2)			
		LDE1 ⁵ - Lutron Hi-Lume 1% Ecosystem with Soft-on, Fade-to-Black Dimming			
		L3DA ⁵ - Hi-Lume 1% Ecosystem/3-Wire L3D Driver			
		PEQO - Lutron Hi-Lume Premier Ecosystem 0.1% with Soft-on, Fade-to-Black Dimming			

Collar	Module Type	Frame Accessories	Options
CR10 - 1.0" Depth	AMHW - Wall Wash	UH - Universal Bar Hanger	ER4W ⁷ - Emergency Battery with Remote test switch (400 lm)
CR15 - 1.5" Depth		C - C-Channel Bar Hanger	ER8W ⁸ - Emergency Battery with Remote test switch (800 lm)
MTO - Made To Order			ER15W ⁸ - Emergency Battery with Remote test switch (1,500 lm)
			347V - 347V Step down transformer
			CP ⁹ - Chicago Plenum

TRIM ORDERING INFORMATION

DIE-CAST

Bevel / Flange Finish	Trim Type	Bevel	Flange
May be mixed and matched	3RFA-CL	W - White	W - White
	3RFA-CL	B - Black	B - Black
	3RFA-CL	H - Haze	BZ - Bronze
	3RFA-CL	BZ - Bronze	MTO - Made To Order
	3RFA-CL		MTO - Made To Order

Notes

1. Not available in IC housing.
2. Intelligent Drive is the standard driver.
3. Must specify logarithmic or linear eldoLED driver.
4. Available up to 20W and programmable only in linear mode.
5. Not offered in 6W.
6. Not available in 28W and 32W.
7. Available in IC housing only.
8. Ceiling access is required for IC housing to replace the EM unit.
9. Requires IC housing.

SPUN ALUMINUM (SELF-FLANGED)

Bevel / Flange Finish	Trim Type	Self-Flanged
	3RFA-AL	H - Haze
	3RFA-AL	C - Clear
	3RFA-AL	MTO - Made To Order

3" LED ARCHITECTURAL ROUND FLANGE WALL WASH

NEW CONSTRUCTION: IC & NON IC

PERFORMANCE CHART

Optics		15°	24°	36°	50°	80°
6W	Initial Lumens	995	955	955	955	955
	Delivered Lumens	598	647	659	616	417
9W	Initial Lumens	1296	1296	1296	1296	1296
	Delivered Lumens	815	879	899	837	566
12W	Initial Lumens	1618	1618	1618	1618	1618
	Delivered Lumens	1025	1101	1134	1048	709
15W	Initial Lumens	2015	2015	2015	2015	2015
	Delivered Lumens	1262	1338	1365	1275	865
20W	Initial Lumens	2422	2422	2422	2422	2422
	Delivered Lumens	1505	1624	1660	1553	1024
24W	Initial Lumens	2799	2799	2799	2799	2799
	Delivered Lumens	1764	1899	1948	1825	1221
28W	Initial Lumens	3128	3128	3128	3128	3128
	Delivered Lumens	2028	2176	2249	2108	1372
32W	Initial Lumens	3405	3405	3405	3405	3405
	Delivered Lumens	2309	2502	2582	2438	1549

* Values are listed at 3000K, 90+ CRI with a white bevel & trim.

COLOR TEMPERATURE MULTIPLIER FOR DELIVERED LUMENS

2700K	3000K	3500K	4000K
0.95	1.00	1.04	1.07

DIFFUSED LENS


- Listed IES files are with diffused lens

3" LED ARCHITECTURAL ROUND FLANGE WALL WASH

NEW CONSTRUCTION: IC & NON IC



NON-IC HOUSING DIMENSIONS 6W-20W

Mounting Bracket up and down adjustability is $2\frac{1}{8}$ "



NC - Non-IC New Construction


Universal bar hanger mounts on the length or width side of the fixture;
Ceiling mount bracket provides 1" adjustability.



1. Must remove spacer to achieve $1\frac{1}{2}$ " collar height
2. Consult factory for Made to Order collar height
3. Allow $\frac{1}{8}$ " tolerance



NON-IC HOUSING DIMENSIONS 24W-32W

Mounting Bracket up and down adjustability is $2\frac{1}{8}$ "



NC - Non-IC New Construction


Universal bar hanger mounts on the length or width side of the fixture;
Ceiling mount bracket provides 1" adjustability.



1. Must remove spacer to achieve $1\frac{1}{2}$ " collar height
2. Consult factory for Made to Order collar height
3. Allow $\frac{1}{8}$ " tolerance



IC HOUSING DIMENSIONS 6W-24W

Mounting Bracket up and down adjustability is $2\frac{1}{8}$ "



IC - IC Air-Tight New Construction

Universal bar hanger mounts on the length or width side of the fixture;
Ceiling mount bracket provides 1" adjustability.






3" LED ARCHITECTURAL ROUND FLANGE WALL WASH

NEW CONSTRUCTION: IC & NON IC

FRAME ACCESSORIES**UNIVERSAL BAR HANGER****COMPATIBLE CEILING**

- Hat Channel
- T-Bar
- C-Channel
- Laminated Wood
- Quick-Span
- I-Beam
- Standard Joist




**C-CHANNEL BAR HANGER****MODULE DIMENSIONS**

3" LED ARCHITECTURAL ROUND FLANGE WALL WASH

NEW CONSTRUCTION: IC & NON IC

TRIM DIMENSIONS

DIE-CAST






TRIM FINISH

May be mixed and matched




*Consult Factory for Made to Order Finishes

SPUN ALUMINUM (SELF-FLANGED)




TRIM FINISH



*Consult Factory for Made to Order Finishes


3" LED ARCHITECTURAL ROUND FLANGE WALL WASH

NEW CONSTRUCTION: IC & NON IC

REMOTE EMERGENCY BATTERY: NON-IC NEW CONSTRUCTION HOUSING**NC - Non-IC New Construction**


ER8W and **ER15W** is an 8W and 15W Emergency Battery that is remote to the fixture with a remote test switch. The EM unit is accessible from below the ceiling for replacement purposes.

1. Remote Emergency Battery
2. Remote Test Switch

REMOTE EMERGENCY BATTERY: IC NEW CONSTRUCTION HOUSING**IC - IC Air-Tight New Construction**

ER8W and **ER15W** is an 8W and 15W Emergency Battery that is remote to the fixture with a remote test switch. Ceiling access is required for replacement purposes

1. Remote Emergency Battery
2. Remote Test Switch

INTEGRAL EMERGENCY BATTERY: IC NEW CONSTRUCTION HOUSING**IC - IC Air-Tight New Construction**

ER4W is an 4W Emergency Battery that is integral to the fixture with a remote test switch. The EM unit is accessible from below the ceiling for replacement purposes.

*Available in IC housing only

1. Integral Emergency Battery
2. Remote Test Switch